

Echo - 2" Recessed Downlight



PROJECT: _____

Type: _____



Product Description

The Echo Downlight is a compact 2" recessed spotlight featuring a fully directional cylindrical head for maximum aiming flexibility. Designed for precision accenting in retail, hospitality, and luxury residential spaces, its bold, architectural form delivers both performance and presence. Ideal when lighting needs to be both seen and shaped.

Features:

- 2" aperture with high-output COB LED
- 360° rotation and up to 20° tilt for full adjustability
- Cylindrical head design for bold architectural expression
- Field-selectable beam angles and CCT options
- Low-glare regressed lens with black or white reflector
- Compatible with TRIAC, ELV, or 0-10V dimming
- Trimmed and trimless options available
- Die-cast aluminum heat sink for thermal stability
- Quick driver access for maintenance

Specifications

Input Voltage: 120-277Vac, 50-60Hz
Power Consumption: 10W
Delivered lumen: 995lm@4000K
CRI(Ra): >90
R9: >70 min
Dimming: TRIAC, ELV or 0-10V
Power Factor: >0.9
Lumen Maintenance: 70% @ 60,000 Hrs
Approved location: IP20, Dry
Tilt : 20°
THD <20%
Certification: cETLus

Critical Dimensions

Cut Out: 2.12" (60mm)
Outer Diameter: 2.68" (68mm)
Ceiling Clearance: 3.15" (90mm)

Ordering Guide

Product	Driver Output	Light Source	Beam Spread	Trim	Baffle finish	Installation
S21	10E-10W TRIAC/ELV 10V-10W 0-10V	40 - 4000K, CRI>90 35 - 3500K, CRI>90 30 - 3000K, CRI>90 27 - 2700K, CRI>90	NS - 16°Narrow Spot SP - 25°Spot FD - 35°Flood WF - 50°Wide Flood	WH - White Flange BK - Black Flange TR - Plaster Trimless C - Custom	WH - White BK - Black C - Custom	RM - Remodel RP - Rough-in Plate NCP- New Construction Non IC

Example:SG-S21-15E-30T-SP-WH-WH-RM



Assembled in
Canada


Specifications and product details provided in this document are subject to change without notice. All product performance values are typical and may vary slightly. Vyyd Lighting assumes no liability for damages or loss resulting from the use of this information. It is the responsibility of the user to verify all data and ensure suitability for the specific application.

Echo - 2" Recessed Downlight



PROJECT: _____ Type: _____


Dimensions




Lumens: Tested with 10W 4000K

Beam angle:	Delivered Lumens:
16°	580lm
25°	790lm
35°	920lm
50°	995lm

NCP- New Construction Non IC



RP - Rough-in Plate



Specifications and product details provided in this document are subject to change without notice. All product performance values are typical and may vary slightly. Vyyvd Lighting assumes no liability for damages or loss resulting from the use of this information. It is the responsibility of the user to verify all data and ensure suitability for the specific application.