




Mi Boxer

2.4GHz Low Voltage LED Controller
Remote Control & Smartphone App
DC12V~24V (RGB+CCT)

5 in 1 Smart LED Controller




Model	Input Voltage	Output	Total Output	Working Temp.	Control Method	Remote Control Distance
LS2	DC12V~24V	6A/Channel	Max 15A	-20~60°C	2.4G	30m

2.4 GHz Gateway



Scan QR Code to Install APP
or search "MiBoxer Smart" on Google Play and
Apple APP store



Model	Input Voltage	Transmitting Power	Working Temp.	Communication Mode	RF	Remote Control Distance
WL-Box1	DC5V/500mA (Micro USB)	6dBm	-20~60°C	WiFi-IEEE 802.11b/g/n 2.4GHz	2.4GHz	30m



Specification Sheet



Rainbow Remote

Model	S2-W	S2-B	S2-G
Color	White	Black	Grey

Working Voltage: 3V(AAA * 2PCS) RF: 2.4GHz
Standby Power: 15µA Control Distance: 30m
Size(mm): Ø70 * 24



Sunrise Remote

Model	S1-W	S1-B	S1-G
Color	White	Black	Grey

Working Voltage: 3V(AAA * 2PCS) RF: 2.4GHz
Standby Power: 15µA Control Distance: 30m
Size(mm): Ø70 * 24



8-Zone RGB+CCT Panel Remote

Model	B8
Color	White

Working Voltage: 3V(AAA*2PCS)/DC3.3V RF: 2.4GHz
Standby Power: 20µA Control Distance: 30m
Group Number: 8-Zone Size(mm): 106 * 146 * 20



8-Zone RGB+CCT Remote

Model	FUT089	FUT089-B
Color	White	Black

Working Voltage: 3V(AAA * 2PCS) RF: 2.4GHz
Standby Power: 15µA Control Distance: 30m
Group Number: 8-Zone Size(mm): 47 * 19 * 153